

# Wet ESP Water Treatment



Jim Cash

Presented to:

Panel & Engineered Lumber International Conference

April 7-8, 2016

Atlanta, Georgia

#### DISCLAIMER

The Babcock & Wilcox Company (B&W) assumes no liability or responsibility with respect to the use of, or for damages resulting from the use of, any information, methods, processes, or recommendations provided in this presentation. B&W expressly excludes and disclaims any and all warranties, whether expressed or implied, which might arise or apply under law or equity or custom or usage of trade, including, without limitation, any warranties of merchantability and/or fitness for a particular or intended purpose.

**Google “WESP”**

**Search “WESP water treatment”**


# Effects of good water treatment



# Trump




# Wood Dryer






# Wet ESP Water Treatment



# Wet ESP Flushing



# Effects of No Suspended Solids Removal Device (Centrifuge Off and Blowdown On)

Time (Hours)	TSS (% by wt)	Notes
0	2.0	<ul style="list-style-type: none"> <li>Normal operating TSS with working centrifuge</li> <li>Solids removal device goes down</li> </ul>
2	2.5	<ul style="list-style-type: none"> <li>Slightly elevated solids due to solids removal device offline</li> </ul>
6	3.5	<ul style="list-style-type: none"> <li>Increased dropout of solids in low velocity areas of piping, vessels and ducts</li> </ul>
12	4.7	<ul style="list-style-type: none"> <li>Plugging of instruments increasingly likely</li> </ul>
16	5.3	<ul style="list-style-type: none"> <li>Blowdown nozzle(s) with fine orifices may start to plug, compounding solids buildup in system</li> </ul>
24	6.4	<ul style="list-style-type: none"> <li>Larger agglomerated pieces may be present due to dislodged sediment plugging basket strainers and nozzles</li> </ul>
60	8.7	<ul style="list-style-type: none"> <li>Less quench water as lines, nozzles and strainers plug leading to unsaturated exhaust feed to wet ESP</li> <li>Further dries particulate on surfaces making it harder to wash off during flushing</li> </ul>
168	9.8	<ul style="list-style-type: none"> <li>Extended running at high solids will erode pumps, cause mechanical seals leaks and further degrade efficiency of the wet ESP</li> <li>Manual cleanouts become much more time consuming (days rather than hours).</li> <li>Failures, alarms and system shutdown probable.</li> <li>Suspended solids reaching equilibrium.</li> </ul>



# Effects of No Blowdown on TDS (Centrifuge On and Blowdown Off)

Time (Hours)	TDS (% by wt)	Notes
0	2.0	Already elevated Total Solids (TS) at 3.5 – 4% by wt when target TS is 3% by wt
16	3.1	<ul style="list-style-type: none"> <li>Increasing tendency to foam</li> </ul>
48	5.3	<ul style="list-style-type: none"> <li>Pump mechanical seals may start to leak due to salt deposits</li> </ul>
120	9.9	<ul style="list-style-type: none"> <li>pH continues to rise as caustic builds up in the system.</li> <li>More caustic allows more tars, pitches, and oils to become dissolved compounding the problems.</li> </ul>
144	11.3	<ul style="list-style-type: none"> <li>Less soluble salts may precipitate out of solution and create deposits, cause erosion of rotating equipment, etc.</li> </ul>
168	12.7	<ul style="list-style-type: none"> <li>No equilibrium attained</li> <li>Dissolved solids continue to accumulate in the system.</li> <li>At some point, certain salts will accumulate to concentrations which may begin to corrode or pit stainless steel.</li> </ul>

# Effects of Using Blowdown for Solids Removal (No Suspended Solids Removal, Just Blowdown)

Blowdown Flow (GPM)	TS (% by wt) at equilibrium	Notes
2	22.8	<ul style="list-style-type: none"> <li>Handling solids concentrations at or above this level involves considerable capital and operating costs</li> <li>Economics are questionable</li> </ul>
4	12.8	<ul style="list-style-type: none"> <li>Within normal blowdown rate range to manage TDS if centrifuge operating</li> </ul>
6	8.9	<ul style="list-style-type: none"> <li>Within normal blowdown rate range to manage TDS if centrifuge operating</li> </ul>
8	6.9	<ul style="list-style-type: none"> <li>Within normal blowdown rate range to manage TDS if centrifuge operating</li> </ul>
18	3.2	<ul style="list-style-type: none"> <li>Minimum recommended blowdown for healthy wastewater system</li> </ul>
20	2.9	<ul style="list-style-type: none"> <li>Double the normal system makeup water usage</li> <li>(~20 gpm blowdown plus ~20 gpm evaporative losses)</li> </ul>
25	2.3	<ul style="list-style-type: none"> <li>Further lowering of TS percentage may allow a more trouble-free operation at the cost of additional makeup water.</li> <li>Consider condensing more water out of the saturated gas stream on wet ESP outlet to offset makeup water demand.</li> </ul>

# Critical Parameters to Monitor for Maintaining a Healthy System

- ▶ **pH** – monitor via continuous in situ pH probe or manual daily pH sampling
- ▶ **Temperature** – monitor via thermocouple or similar
- ▶ **Quench Flow** – monitor liquid flow to nozzles
  - compare with saturation temperature on wet ESP inlet
- ▶ **Flush Water Temperature** – monitor and maximize for best cleaning

# Critical Parameters to Monitor – Manually Drawn Samples

Monitor Via Daily Waste Water Sampling

- ▶ **Total solids (TS) concentration**
- ▶ **Suspended solids (TSS) concentration**
- ▶ **Dissolved solids (TDS) concentration**

# Chemical Addition

## ▶ Typical

- Caustic
- Defoamer

## ▶ Other

- Flocculants and Coagulants
- Acid

# Operation with Water Treatment System Under Control






# Operation with Water Treatment System Out of Control





# Coarse Particulate Removal



# Static Inclined Screens




# Internally Fed Rotary Screen



Parkson Rotoshear®


# Nozzle Protection



# Multiple Basket Strainers




# Fine Particulate Removal






# Centrifuge






# Sweco Centrifuge Overview



# Internal Bowl with Radial Screw Conveyor



# Centrifuge Internals




**Conveyor**



**Bowl**

# DecaPress General Arrangement





# Centrifuge Operation

- ▶ Typical wet cake solids from well maintained and controlled centrifuge in wood products WESP wastewater application
- ▶ Extreme case - excessively wet solids (thickened process wastewater) from centrifuge in wood products WESP wastewater application



# Centrifuge Control

Setting	Increase	Decrease
<b>Bowl speed</b>	<ul style="list-style-type: none"> <li>• G-force increases</li> <li>• Solids removal efficiency improves</li> <li>• Cut point improves</li> <li>• Drier solids</li> </ul>	<ul style="list-style-type: none"> <li>• G-force decreases</li> <li>• Solids removal efficiency degrades</li> <li>• Cut point degrades</li> <li>• Wetter solids</li> </ul>
<b>Feed rate</b>	<ul style="list-style-type: none"> <li>• Less fluid retention time</li> <li>• Solids removal efficiency degrades</li> <li>• Cut point degrades</li> <li>• Wetter solids</li> </ul>	<ul style="list-style-type: none"> <li>• More fluid retention time</li> <li>• Solids removal efficiency improves</li> <li>• Cut point improves</li> <li>• Drier solids</li> </ul>

# Centrifuge Control

Setting	Increase	Decrease
<b>Differential speed</b>	<ul style="list-style-type: none"> <li>• Less solids retention time</li> <li>• Wetter solids</li> <li>• Less torque on gearbox</li> </ul>	<ul style="list-style-type: none"> <li>• More solids retention time</li> <li>• Drier solids</li> <li>• More torque on gearbox</li> </ul>
<b>Feed tube position in bowl</b>	<ul style="list-style-type: none"> <li>• Feed tube in</li> <li>• Drier solids</li> <li>• More torque on gearbox</li> </ul>	<ul style="list-style-type: none"> <li>• Feed tube out (8 in. or 200 mm max)</li> <li>• Wetter solids</li> <li>• Less torque on gearbox</li> </ul>
<b>Pool depth</b>	<ul style="list-style-type: none"> <li>• More fluid retention time</li> <li>• Cut point improves</li> <li>• Wetter solids</li> <li>• Motor load increases</li> </ul>	<ul style="list-style-type: none"> <li>• Less fluid retention time</li> <li>• Cut point degrades</li> <li>• Drier solids</li> <li>• Motor load decreases</li> </ul>



# Centrifuge Maintenance – Daily/Weekly

Frequency	Task	Time Required (Estimated)
Daily	<ul style="list-style-type: none"> <li>• Grease pillow block bearings</li> <li>• Grease nave bearings</li> </ul>	10 minutes
Weekly	<ul style="list-style-type: none"> <li>• Grease pillow block and internal conveyor bearings (100 hrs.)</li> <li>• Check oil level in gearbox</li> <li>• Thorough cleaning of unit and check solids discharge bushings for wear, check wear shield in cover, and check magnetic plugs in gearbox for metal particulate</li> <li>• Check belt tension</li> </ul>	1 hour


# Centrifuge Maintenance – Longer Term/Periodic

Frequency	Task	Time Required (Estimated)
<b>Monthly</b>	<ul style="list-style-type: none"> <li>• Check oil level hydraulic coupling</li> <li>• Change gearbox oil</li> <li>• Measure scroll wear and record. Trend data to predict when rebuild will be necessary.</li> </ul>	1 hour
<b>4 months</b>	<ul style="list-style-type: none"> <li>• Change gearbox oil</li> <li>• Change hydraulic coupling oil</li> </ul>	30 minutes
<b>18 months</b>	<ul style="list-style-type: none"> <li>• Rebuild conveyor?</li> <li>• Change bearings?</li> </ul>	Varies – from hours to change bearings to a week or more if unit must be sent to manufacturer for rebuilding


# Paper Filter



# Paper Filter



# Paper Filter on Dryer System





# Not WESP water treatment



# Wet ESP Water Treatment

**B&W**

MEGTEC

Thank You